

MzScheme: Legacy Module Language

Version 4.0

June 11, 2008

```
(require mzscheme)
```

The `mzscheme` language provides nearly the same bindings as the `mzscheme` module of PLT Scheme version 372 and earlier.

Unlike old version, the `mzscheme` language does not include `set-car!` or `set-cdr!`, and `cons` makes immutable pairs, as in `scheme/base`; those changes make modules built on `mzscheme` reasonably compatible with modules built on `scheme/base`.

Otherwise, the `mzscheme` language shares many bindings with `scheme/base`. It renames a few bindings, such as `syntax-object->datum` instead of `syntax->datum`, and it provides old versions of some syntactic forms, such as `lambda` without support for keyword and optional arguments.

Contents

1	Old Syntactic Forms	3
2	Old Functions	6

1 Old Syntactic Forms

```
(#%module-begin form ...)
```

Like `#%plain-module-begin` from `scheme/base`, but `(require-for-syntax mzscheme)` is added to the beginning of the *form* sequence, thus importing `mzscheme` into the transformer environment for the module body. (In contrast, `scheme/base` exports `for-syntax` minimal transformer support, while `scheme` exports all of `scheme/base` `for-syntax`.)

```
(#%plain-module-begin form ...)
```

The same binding as `#%plain-module-begin` from `scheme/base`.

```
(#%plain-lambda formals body ...+)
```

The same binding as `#%plain-lambda` in `scheme/base`. (This binding was not present in version 372 and earlier.)

```
(lambda formals body ...+)  
(λ formals body ...+)
```

The same bindings as `#%plain-lambda`.

```
(#%app proc-expr arg-expr ...)  
(#%app)
```

The same binding as `#%plain-app` from `scheme/base`.

```
(#%plain-app proc-expr arg-expr ...)  
(#%plain-app)
```

The same binding as `#%app`. (This binding was not present in version 372 and earlier.)

```
(define id expr)  
(define (head args) body ...+)
```

```
head = id
      | (head args)

args = arg-id ...
      | arg-id ... . rest-id
```

Like `define` in `scheme/base`, but without support for keyword arguments or optional arguments.

```
(if test-expr then-expr else-expr)
(if test-expr then-expr)
```

Like `if` in `scheme/base`, but `else-expr` defaults to `(void)`.

```
(cond cond-clause ...)
(case val-expr case-clause ...)
```

Like `cond` and `case` in `scheme/base`, but `else` and `=>` are recognized as unbound identifiers, instead of as the `scheme/base` bindings.

```
(fluid-let ([id expr] ...) body ...+)
```

Provides a kind of dynamic binding via mutation of the `ids`.

The `fluid-let` form first evaluates each `expr` to obtain an *entry value* for each `id`. As evaluation moves into `body`, either through normal evaluation or a continuation jump, the current value of each `id` is swapped with the entry value. On exit from `body`, then the current value and entry value are swapped again.

```
(define-struct id-maybe-super (field-id ...) maybe-inspector-expr)
```

```
maybe-inspector-expr =
  | expr
```

Like `define-struct` from `scheme/base`, but with fewer options. Each field is implicitly mutable, and the optional `expr` is analogous to supplying an `#:inspector` expression.

```
(let-struct id-maybe-super (field-id ...) body ...+)
```

Expands to

```
(let (
```

```
(define-struct id-maybe-super (field-id ...))  
  body ...+)
```

```
(require raw-require-spec)  
(require-for-syntax raw-require-spec)  
(require-for-template raw-require-spec)  
(require-for-label raw-require-spec)  
(provide raw-provide-spec)  
(provide-for-syntax raw-provide-spec)  
(provide-for-label raw-provide-spec)
```

Like `require` and `provide`. The `-for-syntax`, `-for-template`, and `-for-label` forms are translated to `require` and `provide` using `for-syntax`, `for-template`, and `for-label` sub-forms, respectively.

```
(#%datum . datum)
```

Expands to `'datum`, even if `datum` is a keyword.

```
(#%top-interaction . form)
```

The same as `top-interaction` in `scheme/base`.

2 Old Functions

```
(apply proc v ... lst) → any
  proc : procedure?
  v : any/c
  lst : list?
```

Like `apply` from `scheme/base`, but without support for keyword arguments.

```
(open-input-file file [mode]) → input-port?
  file : path-string?
  mode : (one-of/c 'text 'binary) = 'binary
(open-output-file file [mode exists]) → input-port?
  file : path-string?
  mode : (one-of/c 'text 'binary) = 'binary
  exists : (one-of/c 'error 'append 'update
               'replace 'truncate 'truncate/replace)
           = 'error
(open-input-output-file file [mode exists])
→ input-port? output-port?
  file : path-string?
  mode : (one-of/c 'text 'binary) = 'binary
  exists : (one-of/c 'error 'append 'update
               'replace 'truncate 'truncate/replace)
           = 'error
(with-input-from-file file thunk [mode]) → any
  file : path-string?
  thunk : (-> any)
  mode : (one-of/c 'text 'binary) = 'binary
(with-output-to-file file thunk [mode exists]) → any
  file : path-string?
  thunk : (-> any)
  mode : (one-of/c 'text 'binary) = 'binary
  exists : (one-of/c 'error 'append 'update
               'replace 'truncate 'truncate/replace)
           = 'error
(call-with-input-file file proc [mode]) → any
  file : path-string?
  proc : (input-port? -> any)
  mode : (one-of/c 'text 'binary) = 'binary
(call-with-output-file file proc [mode exists]) → any
  file : path-string?
  proc : (output-port? -> any)
  mode : (one-of/c 'text 'binary) = 'binary
```

```

exists : (one-of/c 'error 'append 'update
            'replace 'truncate 'truncate/replace)
        = 'error

```

Like `open-input-file`, etc. from `scheme/base`, but `mode` and `exists` arguments are not keyword arguments. When both `mode` and `exists` are accepted, they are accepted in either order.

```

(syntax-object->datum stx) → any
  stx : syntax?
(datum->syntax-object ctxt v srcloc [prop cert]) → syntax?
  ctxt : (or/c syntax? false/c)
  v : any/c
  srcloc : (or/c syntax? false/c
            (list/c any/c
                  (or/c exact-positive-integer? false/c)
                  (or/c exact-nonnegative-integer? false/c)
                  (or/c exact-nonnegative-integer? false/c)
                  (or/c exact-positive-integer? false/c))
            (vector/c any/c
                      (or/c exact-positive-integer? false/c)
                      (or/c exact-nonnegative-integer? false/c)
                      (or/c exact-nonnegative-integer? false/c)
                      (or/c exact-positive-integer? false/c)))
  prop : (or/c syntax? false/c) = #f
  cert : (or/c syntax? false/c) = #f

```

The same as `syntax->datum` and `datum->syntax`.

```

(module-identifier=? a-id b-id) → boolean?
  a-id : syntax?
  b-id : syntax?
(module-transformer-identifier=? a-id b-id) → boolean?
  a-id : syntax?
  b-id : syntax?
(module-template-identifier=? a-id b-id) → boolean?
  a-id : syntax?
  b-id : syntax?
(module-label-identifier=? a-id b-id) → boolean?
  a-id : syntax?
  b-id : syntax?
(free-identifier=? a-id b-id) → boolean?
  a-id : syntax?
  b-id : syntax?

```

The `module-identifier=?`, etc. functions are the same as `free-identifier=?`, etc. in `scheme/base`.

The `free-identifier=?` procedure returns

```
(and (eq? (syntax-e a) (syntax-e b))
      (module-identifier=? a b))
```

```
(make-namespace [mode]) → namespace?
  mode : (one-of/c 'initial 'empty) = 'initial
```

Creates a namespace with `mzscheme` attached. If the `mode` is empty, the namespace's top-level environment is left empty. If `mode` is `'initial`, then the namespace's top-level environment is initialized with `(namespace-require/copy 'mzscheme)`. See also `make-base-empty-namespace`.

```
(namespace-transformer-require req) → void?
  req : any/c
```

Equivalent to `(namespace-require '(for-syntax ,req))`.

```
(transcript-on filename) → any
  filename : any/c
(transcript-off) → any
```

Raises `exn:fail`, because the operations are not supported.

```
(hash-table? v flag ...) → hash-table?
  v : any/c
  flag : (one-of/c 'weak 'equal)
```

Returns `#t` if `v` like a hash table created by `make-hash-table` or `make-immutable-hash-table` with the given `flags` (or more), `#f` otherwise. Each provided `flag` must be distinct; if the second `flag` is redundant, the `exn:fail:contract` exception is raised.

```
(make-hash-table flag ...) → hash-table?
  flag : (one-of/c 'weak 'equal)
```

Creates and returns a new hash table. If provided, each `flag` must one of the following:

- `'weak` — creates a hash table with weakly-held keys via `make-weak-hash` or `make-weak-hasheq`

- `'equal` — creates a hash table that compares keys using `equal?` instead of `eq?` using `make-hash` or `make-weak-hash`.

By default, key comparisons use `eq?`. If the second `flag` is redundant, the `exn:fail:contract` exception is raised.

```
(make-immutable-hash-table assocs flag ...)  
→ (and/c hash-table? immutable?)  
  assocs : (listof pair?)  
  flag : (one-of/c 'equal)
```

Like `make-immutable-hash` or `make-immutable-hasheq`, depending on whether an `'equal` `flag` is provided.