

S_LTeX Wrapper

Version 4.1.1

October 5, 2008

```
(require slatex/slatex-wrapper)
```

To use S_LTeX as a standalone program, either drag your ".tex" file onto S_LTeX (under Windows or MacOS X), or type `slatex file` in a command shell.

In addition to the S_LTeX tools, this collection contains a parallel set of PDF-S_LTeX tools, which are identical except that they call `pdf-latex` rather than `latex`. In particular, there is now a launcher called (PDF-S_LTeX/pdf-slatex).

```
(slatex filename) → boolean?  
  filename : string?  
(pdf-slatex filename) → boolean?  
  filename : string?
```

Accepts a string naming a file and runs `slatex` and `latex` on the file. It calls `filename->latex-filename` on `filename`.

`pdf-slatex` is like `slatex` except that it calls `pdf-latex` rather than `latex`, and produces PDF output instead of PS output.

```
(slatex/no-latex filename) → void?  
  filename : string?
```

Runs `slatex` on the file named by `filename`, without calling `latex`. That is, it only processes the ".tex" file to produce the ".Z" files. It calls `filename->latex-filename` on `filename`.

```
(latex filename) → boolean?  
  filename : string?
```

```
(pdf-latex filename) → boolean?  
  filename : string?
```

Runs `latex` on the file named by `filename`. It calls `filename->latex-filename` on `filename`.

`pdf-latex` is like `latex` except that it calls `pdf-latex` rather than `latex`, and produces PDF output instead of PS output.

```
(filename->latex-filename filename) → string?  
  filename : string?
```

Accepts a filename and, if that file exists, it returns it. If the filename appended with the suffix `".tex"` exists, that filename is returned. Otherwise, an exception is raised.

NOTE: in order to run `slatex`, your `TEXINPUTS` environment variable must contain a reference to the directory in which the most recent version of `"slatex.sty"` lives. That file resides by default in the `"slatex"` collection of the main installation.