

# R<sup>6</sup>RS: Standard Language

Version 4.1

August 12, 2008

The The Revised<sup>6</sup> Report on the Algorithmic Language Scheme defines a dialect of Scheme. We use *R<sup>6</sup>RS* to refer to both the standard and the language defined by the standard.

R<sup>6</sup>RS defines both *libraries* and *top-level programs*. Both correspond to PLT Scheme *modules* (see §6 “Modules”). That is, although R<sup>6</sup>RS defines top-level programs as entry points, you can just as easily treat a library as an entry point when using PLT Scheme. The only difference is that an R<sup>6</sup>RS top-level program cannot export any bindings to other modules.

# Contents

<b>1</b>	<b>Running Top-Level Programs</b>	<b>4</b>
<b>2</b>	<b>Installing Libraries</b>	<b>5</b>
<b>3</b>	<b>Libraries and Collections</b>	<b>6</b>
<b>4</b>	<b>Scheme Interoperability</b>	<b>7</b>
<b>5</b>	<b>R<sup>6</sup>RS Conformance</b>	<b>8</b>
<b>6</b>	<b>R<sup>6</sup>RS Libraries</b>	<b>9</b>
6.1	<code>(rnrs base (6))</code> : Base . . . . .	9
6.2	<code>(rnrs unicode (6))</code> : Unicode . . . . .	9
6.3	<code>(rnrs bytevectors (6))</code> : Bytevectors . . . . .	9
6.4	<code>(rnrs lists (6))</code> : List utilities . . . . .	9
6.5	<code>(rnrs sorting (6))</code> : Sorting . . . . .	9
6.6	<code>(rnrs control (6))</code> : Control Structures . . . . .	9
6.7	<code>(rnrs records syntactic (6))</code> : Records: Syntactic . . . . .	10
6.8	<code>(rnrs records procedural (6))</code> : Records: Procedural . . . . .	10
6.9	<code>(rnrs records inspection (6))</code> : Records: Inspection . . . . .	10
6.10	<code>(rnrs exceptions (6))</code> : Exceptions . . . . .	10
6.11	<code>(rnrs conditions (6))</code> : Conditions . . . . .	10
6.12	<code>(rnrs io ports (6))</code> : I/O: Ports . . . . .	10
6.13	<code>(rnrs io simple (6))</code> : I/O: Simple . . . . .	11
6.14	<code>(rnrs files (6))</code> : File System . . . . .	11
6.15	<code>(rnrs programs (6))</code> : Command-line Access and Exit Values . . . . .	11

6.16	<code>(rnrs arithmetic fixnums (6))</code> : Arithmetic: Fixnums . . . . .	11
6.17	<code>(rnrs arithmetic flonums (6))</code> : Arithmetic: Flonums . . . . .	11
6.18	<code>(rnrs arithmetic bitwise (6))</code> : Arithmetic: Bitwise . . . . .	11
6.19	<code>(rnrs syntax-case (6))</code> : Syntax-Case . . . . .	12
6.20	<code>(rnrs hashtables (6))</code> : Hashtables . . . . .	12
6.21	<code>(rnrs enums (6))</code> : Enumerations . . . . .	12
6.22	<code>(rnrs eval (6))</code> : Eval . . . . .	12
6.23	<code>(rnrs mutable-pairs (6))</code> : Mutable Pairs . . . . .	12
6.24	<code>(rnrs mutable-strings (6))</code> : Mutable Strings . . . . .	12
6.25	<code>(rnrs r5rs (6))</code> : R5RS Compatibility . . . . .	13

<b>Index</b>		<b>14</b>
--------------	--	-----------

# 1 Running Top-Level Programs

To run a top-level program, either:

- Use the `plt-r6rs` executable, supplying the file that contains the program on the command line:

```
plt-r6rs <program-file>
```

Additional command-line arguments are propagated as command-line arguments to the program (accessed via [command-line](#)).

To compile the file to bytecode (to speed future runs of the program), use `plt-r6rs` with the `--compile` flag:

```
plt-r6rs --compile <program-file>
```

The bytecode file is written in a "compiled" sub-directory next to *<program-file>*.

For example, if "hi.scm" contains

```
(import (rnrs))
(display "hello\n")
```

then

```
plt-r6rs hi.scm
```

prints "hello."

- Prefix the program with `#!r6rs`, which counts as a comment from the R<sup>6</sup>RS perspective, but is a synonym for `#lang r6rs` from the PLT Scheme perspective. Such files can be run like any other PLT Scheme module, such as using `mzscheme`:

```
mzscheme <program-file>
```

or using DrScheme with the Module language. The file can also be compiled to bytecode using `mzc`:

```
mzc <program-file>
```

For example, if "hi.ss" contains

```
#!r6rs
(import (rnrs))
(display "hello\n")
```

then

```
mzscheme hi.ss
```

prints "hello." Similarly, opening "hi.ss" in DrScheme and clicking Run prints "hello" within the DrScheme interactions window.

## 2 Installing Libraries

To reference an R<sup>6</sup>RS library from a top-level program or another library, it must be installed as a collection-based library in PLT Scheme.

One way to produce an R<sup>6</sup>RS installed library is to create in a collection a file that starts with `#!r6rs` and that contains a `library` form. For example, the following file might be created in a "hello.ss" file within a "examples" collection directory:

```
#!r6rs
(library (examples hello)
 (export greet)
 (import (rnrs)))

(define (greet)
 (display "hello\n"))
```

Alternately, the `plt-r6rs` executable with the `--install` flag accepts a sequence of `library` declarations and installs them into separate files in a collection directory, based on the declared name of each library:

```
plt-r6rs --install <libraries-file>
```

By default, libraries are installed into the user-specific collection directory (see `find-user-collects-dir`). The `--all-users` flag causes the libraries to be installed into the main installation, instead (see `find-collects-dir`):

```
plt-r6rs --install --all-users <libraries-file>
```

See §3 “Libraries and Collections” for information on how R<sup>6</sup>RS library names are turned into collection-based module paths, which determines where the files are written. Libraries installed by `plt-r6rs --install` are automatically compiled to bytecode form.

One final option is to supply a `++path` flag to `plt-r6rs`. A path added with `++path` extends the set of directories that are searched to find a collection (i.e., it sets `current-library-collection-paths`). If `<dir>` contains "duck" and "cow" sub-directories with "duck/feather.sls" and "cow/bell.sls", and if each file is an R<sup>6</sup>RS library prefixed with `#!r6rs`, then `plt-r6rs ++path <dir>` directs the R<sup>6</sup>RS library references `(duck feather)` and `(cow bell)` to the files. Note that this technique does not support accessing "duck.sls" directly within `<dir>`, since the library reference `(duck)` is treated like `(duck main)` for finding the library, as explained in §3 “Libraries and Collections”. Multiple paths can be provided with multiple uses of `++path`; the paths are searched in order, and before the installation’s collections.

### 3 Libraries and Collections

An R<sup>6</sup>RS library name is sequence of symbols, optionally followed by a version as a sequence of exact, non-negative integers. Roughly, such a name is converted to a PLT Scheme module pathname (see §6.3 “Module Paths”) by concatenating the symbols with a `/` separator, and then appending the version integers each with a preceding `-`. As a special case, when an R<sup>6</sup>RS path contains a single symbol (optionally followed by a version), a `main` symbol is effectively inserted after the initial symbol. See below for further encoding considerations.

When an R<sup>6</sup>RS library or top-level program refers to another library, it can supply version constraints rather than naming a specific version. Version constraints are always resolved at compile time by searching the set of installed files.

In addition, when an R<sup>6</sup>RS library path is converted, a file extension is selected at compile time based on installed files. The search order for file extensions is `".mzscheme.ss"`, `".mzscheme.sls"`, `".ss"`, and `".sls"`. When resolving version constraints, these extensions are all tried when looking for matches.

To ensure that all R<sup>6</sup>RS library names can be converted to a unique and distinct library module path, the following conversions are applied to each symbol before concatenating them:

- The symbol is encoded using UTF-8, and the resulting bytes are treated as Latin-1 encoded characters. ASCII letters, digits, `+`, `-`, and `_` are left as-is; other characters are replaced by `%` followed by two lowercase hexadecimal digits. Note that UTF-8 encodes ASCII letters, digits, etc. as themselves, so typical library names correspond to readable module paths.
- If the R<sup>6</sup>RS library reference has two symbol elements and the second one is `main` followed by any number of underscores, then an extra underscore is added to that symbol. This conversion avoids a collision between an explicit `main` and the implicit `main` when a library path has a single symbol element.

Examples (assuming a typical PLT Scheme installation):

```
(rnrs io simple (6)) means (lib "rnrs/io/simple-6.ss")
(rnrs)                means (lib "rnrs/main-6.ss")
(rnrs main)          means (lib "rnrs/main_.ss")
(rnrs (6))           means (lib "rnrs/main-6.ss")
(scheme base)        means (lib "scheme/base.ss")
(achtung!)            means (lib "achtung%21/main.ss")
(funco new-λ)        means (lib "funco/new-%ce%bb.ss")
```

## 4 Scheme Interoperability

Using the conversion rules in §3 “Libraries and Collections”, and R<sup>6</sup>RS library can refer to modules that are implemented in other dialects supported by PLT Scheme, and other PLT Scheme modules can refer to libraries that are implemented in R<sup>6</sup>RS.

Beware that a *pair* in R<sup>6</sup>RS corresponds to a *mutable pair* in `scheme/base`. Otherwise, R<sup>6</sup>RS libraries and `scheme/base` share the same datatype for numbers, characters, strings, bytevectors (a.k.a. byte strings), vectors, and so on. Hash tables are different. Input and output ports from `scheme/base` can be used directly as binary ports with R<sup>6</sup>RS libraries, and all R<sup>6</sup>RS ports can be used as ports in `scheme/base` programs, but only textual ports created via R<sup>6</sup>RS libraries can be used by other R<sup>6</sup>RS operations that expect textual ports.

## 5 R<sup>6</sup>RS Conformance

PLT Scheme's R<sup>6</sup>RS support does not conform with the standard in several known ways:

- When guard catches an exception that no clause matches, the exception is re-`raised` without restoring the continuation to the one that raised the exception.

This difference can be made visible using `dynamic-wind`. According to R<sup>6</sup>RS, the following program should print “in” and “out” twice, but each prints once using PLT Scheme:

```
(guard (exn [(equal? exn 5) 'five]))
  (guard (exn [(equal? exn 6) 'six]))
    (dynamic-wind
      (lambda () (display "in") (newline))
      (lambda () (raise 5))
      (lambda () (display "out") (newline))))))
```

Along similar lines, continuation capture and invocation within an exception handler is restricted. Unless the exception is raised through `raise-continuable`, a handler can escape only through a continuation that is a tail of the current continuation, and a continuation captured within the handler cannot be invoked after control escapes from the raise.

The initial exception handler does not return for non-`&serious` conditions, but `raise` and `raise-continuable` both install an uncaught-exception handler (via `parameterize` and `uncaught-exception-handler`) to one that returns for non-`&serious` conditions.

- Inexact numbers are printed without a precision indicator, and precision indicators are ignored on input (e.g., `0.5|7` is read the same as `0.5`).
- Word boundaries for `string-downcase`, `string-upcase`, and `string-titlecase` are not determined as specified by Unicode Standard Annex #29.
- When an identifier bound by `letrec` or `letrec*` is referenced before it is bound, an exception is not raised; instead, the reference produces `#<undefined>`.
- The bindings in a namespace produced by `null-environment` or `scheme-report-environment` correspond to R<sup>5</sup>RS bindings instead of R<sup>6</sup>RS bindings. In particular, `=>`, `else`, `_`, and `...` are not bound.



## 6 R<sup>6</sup>RS Libraries

### 6.1 `(rnrs base (6))`: Base

`(require rnrs/base-6)`

Original specification: Base

### 6.2 `(rnrs unicode (6))`: Unicode

`(require rnrs/unicode-6)`

Original specification: Unicode

### 6.3 `(rnrs bytevectors (6))`: Bytevectors

`(require rnrs/bytevectors-6)`

Original specification: Bytevectors

### 6.4 `(rnrs lists (6))`: List utilities

`(require rnrs/lists-6)`

Original specification: List utilities

### 6.5 `(rnrs sorting (6))`: Sorting

`(require rnrs/sorting-6)`

Original specification: Sorting

### 6.6 `(rnrs control (6))`: Control Structures

`(require rnrs/control-6)`

Original specification: Control Structures

## **6.7** `(nrns records syntactic (6))`: **Records: Syntactic**

`(require nrns/records/syntactic-6)`

Original specification: Records: Syntactic

## **6.8** `(nrns records procedural (6))`: **Records: Procedural**

`(require nrns/records/procedural-6)`

Original specification: Records: Procedural

## **6.9** `(nrns records inspection (6))`: **Records: Inspection**

`(require nrns/records/inspection-6)`

Original specification: Records: Inspection

## **6.10** `(nrns exceptions (6))`: **Exceptions**

`(require nrns/exceptions-6)`

Original specification: Exceptions

See also §5 “R<sup>6</sup>RS Conformance”.

## **6.11** `(nrns conditions (6))`: **Conditions**

`(require nrns/conditions-6)`

Original specification: Conditions

## **6.12** `(nrns io ports (6))`: **I/O: Ports**

`(require nrns/io/ports-6)`

Original specification: I/O: Ports

### **6.13** `(rnrs io simple (6))`: I/O: Simple

`(require rnrs/io/simple-6)`

Original specification: I/O: Simple

### **6.14** `(rnrs files (6))`: File System

`(require rnrs/files-6)`

Original specification: File System

### **6.15** `(rnrs programs (6))`: Command-line Access and Exit Values

`(require rnrs/programs-6)`

Original specification: Command-line Access and Exit Values

### **6.16** `(rnrs arithmetic fixnums (6))`: Arithmetic: Fixnums

`(require rnrs/arithmetic/fixnums-6)`

Original specification: Arithmetic: Fixnums

### **6.17** `(rnrs arithmetic flonums (6))`: Arithmetic: Flonums

`(require rnrs/arithmetic/flonums-6)`

Original specification: Arithmetic: Flonums

### **6.18** `(rnrs arithmetic bitwise (6))`: Arithmetic: Bitwise

`(require rnrs/arithmetic/bitwise-6)`

Original specification: Arithmetic: Bitwise

## 6.19 `(rnrs syntax-case (6))`: Syntax-Case

```
(require rnrs/syntax-case-6)
```

Original specification: Syntax-Case

## 6.20 `(rnrs hashtables (6))`: Hashtables

```
(require rnrs/hashtables-6)
```

Original specification: Hashtables

A hashtable is a dictionary in the sense of `scheme/dict`.

## 6.21 `(rnrs enums (6))`: Enumerations

```
(require rnrs/enums-6)
```

Original specification: Enumerations

## 6.22 `(rnrs eval (6))`: Eval

```
(require rnrs/eval-6)
```

Original specification: Eval

## 6.23 `(rnrs mutable-pairs (6))`: Mutable Pairs

```
(require rnrs/mutable-pairs-6)
```

Original specification: Mutable Pairs

## 6.24 `(rnrs mutable-strings (6))`: Mutable Strings

```
(require rnrs/mutable-strings-6)
```

Original specification: Mutable Strings

## 6.25 `(nrns r5rs (6))`: R5RS Compatibility

`(require nrns/r5rs-6)`

Original specification: R5RS Compatibility

See also §5 “R<sup>6</sup>RS Conformance”.

## Index

`&assertion`, 10  
`&condition`, 10  
`&error`, 10  
`&i/o`, 10  
`&i/o-decoding`, 10  
`&i/o-encoding`, 10  
`&i/o-file-already-exists`, 10  
`&i/o-file-does-not-exist`, 10  
`&i/o-file-is-read-only`, 10  
`&i/o-file-protection`, 10  
`&i/o-filename`, 10  
`&i/o-invalid-position`, 10  
`&i/o-port`, 10  
`&i/o-read`, 10  
`&i/o-write`, 10  
`&implementation-restriction`, 10  
`&irritants`, 10  
`&lexical`, 10  
`&message`, 10  
`&no-infinities`, 11  
`&no-nans`, 11  
`&non-continuable`, 10  
`&serious`, 10  
`&syntax`, 10  
`&undefined`, 10  
`&violation`, 10  
`&warning`, 10  
`&who`, 10  
`(rnrs arithmetic bitwise (6))`: Arithmetic: Bitwise, 11  
`(rnrs arithmetic fixnums (6))`: Arithmetic: Fixnums, 11  
`(rnrs arithmetic flonums (6))`: Arithmetic: Flonums, 11  
`(rnrs base (6))`: Base, 9  
`(rnrs bytevectors (6))`: Bytevectors, 9  
`(rnrs conditions (6))`: Conditions, 10  
`(rnrs control (6))`: Control Structures, 9  
`(rnrs enums (6))`: Enumerations, 12  
`(rnrs eval (6))`: Eval, 12  
`(rnrs exceptions (6))`: Exceptions, 10  
`(rnrs files (6))`: File System, 11  
`(rnrs hashtables (6))`: Hashtables, 12  
`(rnrs io ports (6))`: I/O: Ports, 10  
`(rnrs io simple (6))`: I/O: Simple, 11  
`(rnrs lists (6))`: List utilities, 9  
`(rnrs mutable-pairs (6))`: Mutable Pairs, 12  
`(rnrs mutable-strings (6))`: Mutable Strings, 12  
`(rnrs programs (6))`: Command-line Access and Exit Values, 11  
`(rnrs r5rs (6))`: R5RS Compatibility, 13  
`(rnrs records inspection (6))`: Records: Inspection, 10  
`(rnrs records procedural (6))`: Records: Procedural, 10  
`(rnrs records syntactic (6))`: Records: Syntactic, 10  
`(rnrs sorting (6))`: Sorting, 9  
`(rnrs syntax-case (6))`: Syntax-Case, 12  
`(rnrs unicode (6))`: Unicode, 9  
`*`, 9  
`+`, 9  
`++path`, 5  
`-`, 9  
`...`, 9  
`...`, 12  
`/`, 9  
`<`, 9  
`<=`, 9  
`=`, 9  
`=>`, 9  
`=>`, 10  
`>`, 9  
`>=`, 9  
`→`, 9  
`→`, 12  
`abs`  
`acos`, 9  
`and`, 9

angle, 9  
 append, 9  
 apply, 9  
 asin, 9  
 assert, 9  
 assertion-violation, 9  
 assertion-violation?, 10  
 assoc, 9  
 assp, 9  
 assq, 9  
 assv, 9  
 atan, 9  
 begin  
 binary-port?, 10  
 bitwise-and, 11  
 bitwise-arithmetic-shift, 11  
 bitwise-arithmetic-shift-left, 11  
 bitwise-arithmetic-shift-right, 11  
 bitwise-bit-count, 11  
 bitwise-bit-field, 11  
 bitwise-bit-set?, 11  
 bitwise-copy-bit, 11  
 bitwise-copy-bit-field, 11  
 bitwise-first-bit-set, 11  
 bitwise-if, 11  
 bitwise-ior, 11  
 bitwise-length, 11  
 bitwise-not, 11  
 bitwise-reverse-bit-field, 11  
 bitwise-rotate-bit-field, 11  
 bitwise-xor, 11  
 boolean=?, 9  
 boolean?, 9  
 bound-identifier=?, 12  
 buffer-mode, 10  
 buffer-mode?, 10  
 bytevector->sint-list, 9  
 bytevector->string, 10  
 bytevector->u8-list, 9  
 bytevector->uint-list, 9  
 bytevector-copy, 9  
 bytevector-copy!, 9  
 bytevector-fill!, 9  
 bytevector-ieee-double-native-ref,  
   9  
 bytevector-ieee-double-native-  
   set!, 9  
 bytevector-ieee-double-ref, 9  
 bytevector-ieee-single-native-ref,  
   9  
 bytevector-ieee-single-native-  
   set!, 9  
 bytevector-ieee-single-ref, 9  
 bytevector-length, 9  
 bytevector-s16-native-ref, 9  
 bytevector-s16-native-set!, 9  
 bytevector-s16-ref, 9  
 bytevector-s16-set!, 9  
 bytevector-s32-native-ref, 9  
 bytevector-s32-native-set!, 9  
 bytevector-s32-ref, 9  
 bytevector-s32-set!, 9  
 bytevector-s64-native-ref, 9  
 bytevector-s64-native-set!, 9  
 bytevector-s64-ref, 9  
 bytevector-s64-set!, 9  
 bytevector-s8-ref, 9  
 bytevector-s8-set!, 9  
 bytevector-sint-ref, 9  
 bytevector-sint-set!, 9  
 bytevector-u16-native-ref, 9  
 bytevector-u16-native-set!, 9  
 bytevector-u16-ref, 9  
 bytevector-u16-set!, 9  
 bytevector-u32-native-ref, 9  
 bytevector-u32-native-set!, 9  
 bytevector-u32-ref, 9  
 bytevector-u32-set!, 9  
 bytevector-u64-native-ref, 9  
 bytevector-u64-native-set!, 9  
 bytevector-u64-ref, 9  
 bytevector-u64-set!, 9  
 bytevector-u8-ref, 9  
 bytevector-u8-set!, 9

bytevector-uint-ref, 9  
 bytevector-uint-set!, 9  
 bytevector=?, 9  
 bytevector?, 9  
 caar  
 cadr, 9  
 call-with-bytevector-output-port,  
   10  
 call-with-current-continuation, 9  
 call-with-input-file, 11  
 call-with-output-file, 11  
 call-with-port, 10  
 call-with-string-output-port, 10  
 call-with-values, 9  
 call/cc, 9  
 car, 9  
 case, 9  
 case-lambda, 9  
 cdddar, 9  
 cddddr, 9  
 cdr, 9  
 ceiling, 9  
 char->integer, 9  
 char-alphabetic?, 9  
 char-ci<=?, 9  
 char-ci<?, 9  
 char-ci=?, 9  
 char-ci>=?, 9  
 char-ci>?, 9  
 char-downcase, 9  
 char-foldcase, 9  
 char-general-category, 9  
 char-lower-case?, 9  
 char-numeric?, 9  
 char-title-case?, 9  
 char-titlecase, 9  
 char-upcase, 9  
 char-upper-case?, 9  
 char-whitespace?, 9  
 char<=?, 9  
 char<?, 9  
 char=?, 9  
 char>=?, 9  
 char>?, 9  
 char?, 9  
 close-input-port, 11  
 close-output-port, 11  
 close-port, 10  
 command-line, 11  
 complex?, 9  
 cond, 9  
 condition, 10  
 condition-accessor, 10  
 condition-irritants, 10  
 condition-message, 10  
 condition-predicate, 10  
 condition-who, 10  
 condition?, 10  
 cons, 9  
 cons\*, 9  
 cos, 9  
 current-error-port, 10  
 current-input-port, 10  
 current-output-port, 10  
 datum->syntax  
 define, 9  
 define-condition-type, 10  
 define-enumeration, 12  
 define-record-type, 10  
 define-syntax, 9  
 delay, 13  
 delete-file, 11  
 denominator, 9  
 display, 11  
 div, 9  
 div-and-mod, 9  
 div0, 9  
 div0-and-mod0, 9  
 do, 9  
 dynamic-wind, 9  
 else  
 else, 10  
 endianness, 9  
 enum-set->list, 12



enum-set-complement, 12  
enum-set-constructor, 12  
enum-set-difference, 12  
enum-set-indexer, 12  
enum-set-intersection, 12  
enum-set-member?, 12  
enum-set-projection, 12  
enum-set-subset?, 12  
enum-set-union, 12  
enum-set-universe, 12  
enum-set=?, 12  
environment, 12  
eof-object, 10  
eof-object?, 10  
eol-style, 10  
eq?, 9  
equal-hash, 12  
equal?, 9  
eqv?, 9  
error, 9  
error-handling-mode, 10  
error?, 10  
eval, 12  
even?, 9  
exact, 9  
exact->inexact, 13  
exact-integer-sqrt, 9  
exact?, 9  
exists, 9  
exit, 11  
exp, 9  
expt, 9  
fields  
file-exists?, 11  
file-options, 10  
filter, 9  
find, 9  
finite?, 9  
fixnum->flonum, 11  
fixnum-width, 11  
fixnum?, 11  
fl\*, 11  
fl+, 11  
fl-, 11  
fl/, 11  
fl<=?, 11  
fl<?, 11  
fl=?, 11  
fl>=?, 11  
fl>?, 11  
flabs, 11  
flacos, 11  
flasin, 11  
flatan, 11  
flceiling, 11  
flcos, 11  
fldenominator, 11  
fldiv, 11  
fldiv-and-mod, 11  
fldiv0, 11  
fldiv0-and-mod0, 11  
fleven?, 11  
flexp, 11  
flexpt, 11  
flfinite?, 11  
flfloor, 11  
flinfinite?, 11  
flinteger?, 11  
fllog, 11  
flmax, 11  
flmin, 11  
flmod, 11  
flmod0, 11  
flnan?, 11  
flnegative?, 11  
flnumerator, 11  
flodd?, 11  
flonum?, 11  
floor, 9  
flpositive?, 11  
flround, 11  
flsin, 11  
flsqrt, 11  
fltand, 11

[fltruncate](#), 11  
[flush-output-port](#), 10  
[flzero?](#), 11  
[fold-left](#), 9  
[fold-right](#), 9  
[for-all](#), 9  
[for-each](#), 9  
[force](#), 13  
[free-identifier=?](#), 12  
[fx\\*](#), 11  
[fx\\*/carry](#), 11  
[fx+](#), 11  
[fx+/carry](#), 11  
[fx-](#), 11  
[fx-/carry](#), 11  
[fx<=?](#), 11  
[fx<?](#), 11  
[fx=?](#), 11  
[fx>=?](#), 11  
[fx>?](#), 11  
[fxand](#), 11  
[fxarithmetic-shift](#), 11  
[fxarithmetic-shift-left](#), 11  
[fxarithmetic-shift-right](#), 11  
[fxbit-count](#), 11  
[fxbit-field](#), 11  
[fxbit-set?](#), 11  
[fxcopy-bit](#), 11  
[fxcopy-bit-field](#), 11  
[fxdiv](#), 11  
[fxdiv-and-mod](#), 11  
[fxdiv0](#), 11  
[fxdiv0-and-mod0](#), 11  
[fxeven?](#), 11  
[fxfirst-bit-set](#), 11  
[fxif](#), 11  
[fxior](#), 11  
[fxlength](#), 11  
[fxmax](#), 11  
[fxmin](#), 11  
[fxmod](#), 11  
[fxmod0](#), 11  
[fxnegative?](#), 11  
[fxnot](#), 11  
[fxodd?](#), 11  
[fxpositive?](#), 11  
[fxreverse-bit-field](#), 11  
[fxrotate-bit-field](#), 11  
[fxxor](#), 11  
[fxzero?](#), 11  
[gcd](#)  
[generate-temporaries](#), 12  
[get-bytevector-all](#), 10  
[get-bytevector-n](#), 10  
[get-bytevector-n!](#), 10  
[get-bytevector-some](#), 10  
[get-char](#), 10  
[get-datum](#), 10  
[get-line](#), 10  
[get-string-all](#), 10  
[get-string-n](#), 10  
[get-string-n!](#), 10  
[get-u8](#), 10  
[greatest-fixnum](#), 11  
[guard](#), 10  
[hashtable-clear!](#)  
[hashtable-contains?](#), 12  
[hashtable-copy](#), 12  
[hashtable-delete!](#), 12  
[hashtable-entries](#), 12  
[hashtable-equivalence-function](#), 12  
[hashtable-hash-function](#), 12  
[hashtable-keys](#), 12  
[hashtable-mutable?](#), 12  
[hashtable-ref](#), 12  
[hashtable-set!](#), 12  
[hashtable-size](#), 12  
[hashtable-update!](#), 12  
[hashtable?](#), 12  
[i/o-decoding-error?](#)  
[i/o-encoding-error-char](#), 10  
[i/o-encoding-error?](#), 10  
[i/o-error-filename](#), 10  
[i/o-error-port](#), 10

*i/o-error-position*, 10  
*i/o-error?*, 10  
*i/o-file-already-exists-error?*, 10  
*i/o-file-does-not-exist-error?*, 10  
*i/o-file-is-read-only-error?*, 10  
*i/o-file-protection-error?*, 10  
*i/o-filename-error?*, 10  
*i/o-invalid-position-error?*, 10  
*i/o-port-error?*, 10  
*i/o-read-error?*, 10  
*i/o-write-error?*, 10  
*identifier-syntax*, 9  
*identifier?*, 12  
*if*, 9  
*imag-part*, 9  
*immutable*, 10  
*implementation-restriction-violation?*, 10  
*inexact*, 9  
*inexact->exact*, 13  
*inexact?*, 9  
*infinite?*, 9  
*input-port?*, 10  
Installing Libraries, 5  
*integer->char*, 9  
*integer-valued?*, 9  
*integer?*, 9  
*irritants-condition?*, 10  
*lambda*  
*latin-1-codec*, 10  
*lcm*, 9  
*least-fixnum*, 11  
*length*, 9  
*let*, 9  
*let\**, 9  
*let\*-values*, 9  
*let-syntax*, 9  
*let-values*, 9  
*letrec*, 9  
*letrec\**, 9  
*letrec-syntax*, 9  
*lexical-violation?*, 10  
Libraries and Collections, 6  
*list*, 9  
*list->string*, 9  
*list->vector*, 9  
*list-ref*, 9  
*list-sort*, 9  
*list-tail*, 9  
*list?*, 9  
*log*, 9  
*lookahead-char*, 10  
*lookahead-u8*, 10  
*magnitude*  
*make-assertion-violation*, 10  
*make-bytevector*, 9  
*make-custom-binary-input-port*, 10  
*make-custom-binary-input/output-port*, 10  
*make-custom-binary-output-port*, 10  
*make-custom-textual-input-port*, 10  
*make-custom-textual-input/output-port*, 10  
*make-custom-textual-output-port*, 10  
*make-enumeration*, 12  
*make-eq-hashtable*, 12  
*make-eqv-hashtable*, 12  
*make-error*, 10  
*make-hashtable*, 12  
*make-i/o-decoding-error*, 10  
*make-i/o-encoding-error*, 10  
*make-i/o-error*, 10  
*make-i/o-file-already-exists-error*, 10  
*make-i/o-file-does-not-exist-error*, 10  
*make-i/o-file-is-read-only-error*, 10  
*make-i/o-file-protection-error*, 10  
*make-i/o-filename-error*, 10  
*make-i/o-invalid-position-error*, 10  
*make-i/o-port-error*, 10  
*make-i/o-read-error*, 10  
*make-i/o-write-error*, 10

make-implementation-restriction-violation, 10  
 make-irritants-condition, 10  
 make-lexical-violation, 10  
 make-message-condition, 10  
 make-no-infinities-violation, 11  
 make-no-nans-violation, 11  
 make-non-continuable-violation, 10  
 make-polar, 9  
 make-record-constructor-descriptor, 10  
 make-record-type-descriptor, 10  
 make-rectangular, 9  
 make-serious-condition, 10  
 make-string, 9  
 make-syntax-violation, 10  
 make-transcoder, 10  
 make-undefined-violation, 10  
 make-variable-transformer, 12  
 make-vector, 9  
 make-violation, 10  
 make-warning, 10  
 make-who-condition, 10  
 map, 9  
 max, 9  
 member, 9  
 memp, 9  
 memq, 9  
 memv, 9  
 message-condition?, 10  
 min, 9  
 mod, 9  
 mod0, 9  
 modulo, 13  
 mutable, 10  
 nan?  
 native-endianness, 9  
 native-eol-style, 10  
 native-transcoder, 10  
 negative?, 9  
 newline, 11  
 no-infinities-violation?, 11  
 no-nans-violation?, 11  
 non-continuable-violation?, 10  
 nongenerative, 10  
 not, 9  
 null-environment, 13  
 null?, 9  
 number->string, 9  
 number?, 9  
 numerator, 9  
 odd?  
 opaque, 10  
 open-bytevector-input-port, 10  
 open-bytevector-output-port, 10  
 open-file-input-port, 10  
 open-file-input/output-port, 10  
 open-file-output-port, 10  
 open-input-file, 11  
 open-output-file, 11  
 open-string-input-port, 10  
 open-string-output-port, 10  
 or, 9  
 output-port-buffer-mode, 10  
 output-port?, 10  
 pair?  
 parent, 10  
 parent-rtd, 10  
 partition, 9  
 peek-char, 11  
 port-eof?, 10  
 port-has-port-position?, 10  
 port-has-set-port-position!?, 10  
 port-position, 10  
 port-transcoder, 10  
 port?, 10  
 positive?, 9  
 procedure?, 9  
 protocol, 10  
 put-bytevector, 10  
 put-char, 10  
 put-datum, 10  
 put-string, 10  
 put-u8, 10

[quasiquote](#)  
[quasisyntax](#), 12  
[quote](#), 9  
[quotient](#), 13  
[R<sup>6</sup>RS Conformance](#)  
[R<sup>6</sup>RS Libraries](#), 9  
**R<sup>6</sup>RS**: Standard Language, 1  
[raise](#), 10  
[raise-continuable](#), 10  
[rational-valued?](#), 9  
[rational?](#), 9  
[rationalize](#), 9  
[read](#), 11  
[read-char](#), 11  
[real->flonum](#), 11  
[real-part](#), 9  
[real-valued?](#), 9  
[real?](#), 9  
[record-accessor](#), 10  
[record-constructor](#), 10  
[record-constructor-descriptor](#), 10  
[record-field-mutable?](#), 10  
[record-mutator](#), 10  
[record-predicate](#), 10  
[record-rtd](#), 10  
[record-type-descriptor](#), 10  
[record-type-descriptor?](#), 10  
[record-type-field-names](#), 10  
[record-type-generative?](#), 10  
[record-type-name](#), 10  
[record-type-opaque?](#), 10  
[record-type-parent](#), 10  
[record-type-sealed?](#), 10  
[record-type-uid](#), 10  
[record?](#), 10  
[remainder](#), 13  
[remove](#), 9  
[remp](#), 9  
[remq](#), 9  
[remv](#), 9  
[reverse](#), 9  
[rnrs/arithmetic/bitwise-6](#), 11  
[rnrs/arithmetic/fixnums-6](#), 11  
[rnrs/arithmetic/flonums-6](#), 11  
[rnrs/base-6](#), 9  
[rnrs/bytevectors-6](#), 9  
[rnrs/conditions-6](#), 10  
[rnrs/control-6](#), 9  
[rnrs/enums-6](#), 12  
[rnrs/eval-6](#), 12  
[rnrs/exceptions-6](#), 10  
[rnrs/files-6](#), 11  
[rnrs/hashtables-6](#), 12  
[rnrs/io/ports-6](#), 10  
[rnrs/io/simple-6](#), 11  
[rnrs/lists-6](#), 9  
[rnrs/mutable-pairs-6](#), 12  
[rnrs/mutable-strings-6](#), 12  
[rnrs/programs-6](#), 11  
[rnrs/r5rs-6](#), 13  
[rnrs/records/inspection-6](#), 10  
[rnrs/records/procedural-6](#), 10  
[rnrs/records/syntactic-6](#), 10  
[rnrs/sorting-6](#), 9  
[rnrs/syntax-case-6](#), 12  
[rnrs/unicode-6](#), 9  
[round](#), 9  
[Running Top-Level Programs](#), 4  
[Scheme Interoperability](#)  
[scheme-report-environment](#), 13  
[sealed](#), 10  
[serious-condition?](#), 10  
[set!](#), 9  
[set-car!](#), 12  
[set-cdr!](#), 12  
[set-port-position!](#), 10  
[simple-conditions](#), 10  
[sin](#), 9  
[sint-list->bytevector](#), 9  
[sqrt](#), 9  
[standard-error-port](#), 10  
[standard-input-port](#), 10  
[standard-output-port](#), 10  
[string](#), 9

- string->bytevector, 10
- string->list, 9
- string->number, 9
- string->symbol, 9
- string->utf16, 9
- string->utf32, 9
- string->utf8, 9
- string-append, 9
- string-ci-hash, 12
- string-ci<=?, 9
- string-ci<?, 9
- string-ci=?, 9
- string-ci>=?, 9
- string-ci>?, 9
- string-copy, 9
- string-downcase, 9
- string-fill!, 12
- string-foldcase, 9
- string-for-each, 9
- string-hash, 12
- string-length, 9
- string-normalize-nfc, 9
- string-normalize-nfd, 9
- string-normalize-nfkc, 9
- string-normalize-nfkd, 9
- string-ref, 9
- string-set!, 12
- string-titlecase, 9
- string-upcase, 9
- string<=?, 9
- string<?, 9
- string=?, 9
- string>=?, 9
- string>?, 9
- string?, 9
- substring, 9
- symbol->string, 9
- symbol-hash, 12
- symbol=?, 9
- symbol?, 9
- syntax, 12
- syntax->datum, 12
- syntax-case, 12
- syntax-rules, 9
- syntax-violation, 12
- syntax-violation-form, 10
- syntax-violation-subform, 10
- syntax-violation?, 10
- tan
- textual-port?, 10
- transcoded-port, 10
- transcoder-codec, 10
- transcoder-eol-style, 10
- transcoder-error-handling-mode, 10
- truncate, 9
- u8-list->bytevector
- uint-list->bytevector, 9
- undefined-violation?, 10
- unless, 9
- unquote, 9
- unquote-splicing, 9
- unsyntax, 12
- unsyntax-splicing, 12
- utf-16-codec, 10
- utf-8-codec, 10
- utf16->string, 9
- utf32->string, 9
- utf8->string, 9
- values
- vector, 9
- vector->list, 9
- vector-fill!, 9
- vector-for-each, 9
- vector-length, 9
- vector-map, 9
- vector-ref, 9
- vector-set!, 9
- vector-sort, 9
- vector-sort!, 9
- vector?, 9
- violation?, 10
- warning?
- when, 9
- who-condition?, 10

`with-exception-handler`, 10  
`with-input-from-file`, 11  
`with-output-to-file`, 11  
`with-syntax`, 12  
`write`, 11  
`write-char`, 11  
`zero?`